Windows Hello compatible webcam with built-in privacy lens cover

JPL Vision Access

- Universal 1080p HD 30fps webcam
- Ideal for use where office security is essential
- Ease of access to your device with Windows Hello facial recognition
- Plug & play solution - No software or downloads needed
- 96° Field of view
- Omnidirectional microphone
- Built-in privacy lens cover
- Built-in camera in-use LED indicator

- USB Type-A and USB Type-C connectivity included
- Multi-angled desk mount / monitor mount (as well as tripod fixing screw option on the base) giving full 360° camera rotation and 90° camera forward tilt
- 2 year standard repair or replacement warranty

Optional mounting suggestion.
Tripod not included

JPL Vision Access

Windows Hello compatible USB webcam with a full HD 1080p glass lens, built-in privacy lens cover, USB-A and USB-C connectivity to allow optional connection to any USB-A or USB-C device.

Compatible with all major softphones.

Plug & play solution - No additional software or downloads needed.

1080p 30 fps | Compatible with Windows Hello | Undistorted Field of View | Integrated Privacy Cover | USB-A / USB-C to USB-C Adapter

Overview

Features	HD 1920 x 1080p Camera
	Full HD 1080p glass lens - No optical distortion
	Built-in privacy lens cover
	Omnidirectional microphone
	Built-in camera in-use LED indicator
	USB 2.0 Type-A and USB-C connectivity
	Desk mount, monitor mount and universal thread for tripod option
	Full 360° camera rotation including 90° tilt for over desk viewing
	Automatic low-light correction
	AEC – Automatic Echo Cancellation
	ANS – Automatic Noise Suppression
Certifications	UKCA, CE, FCC, RoHS, REACH
Unit Dimensions	92.5 x 52 x 31 mm
Warranty	24 Month repair or replacement warranty
MOQ	Master Shipping Carton: 40
SKU:	575-400-001
EAN:	5060126959786

Technical Data

Camera parameters:		
IR Camera SENSOR:	Sensor Type	1/9"CMOS
	Array Size	1280*720 30FPS
	Pixel Size	1.4 µm x 1.4 µm / BSI
RGB Camera SENSOR:	Sensor Type	1/2.9" CMOS
	Array Size	1920*1080P 30FPS
	Pixel Size	2.8µm*2.8µm FSI
IR Lens:	Construction	3P
	IR Filter	850nm
	FOV	D=85±°;
	F/No	2.4±5%
	TV Distortion	<-2.6%
RGB Lens:	Construction	1G4P+IR
	IR Filter	650nm
	FOV	D=96±°
	F/No	2.5±5%
	TV Distortion	<-0.9%
MIC:	Dimensional	Ø4.0*1.5mm
	Sensitivity	-38±3db
	S/N ratio	60db
	Pick-up distance	3m
Temperature(Operation)		-10°c to 60°c
Temperature(Storage)		-10°c to 60°c
USB Power Supply Voltage		DC 5V
Interface		USB 2.0 USB-A/TYPE-C
Operating System Request		Windows 10-11 (Windows Hello)
AGE/AEC/White Balance		Auto
Supports compression formats		MJPEG/YUV